Hand pallet truck 1.0 ton

BT pro lifter m













TOYOTA

MATERIAL HANDLING

www.toyota-forklifts.eu


stronger together

Hand pallet truck

Truck specifications					LHT100
Identification	1.1	Manufacturer			BT
	1.2	Manufacturer's type designation			LHT100
	1.3	Drive			Battery
	1.4	Operator type			Hand
	1.5	Load capacity/rated load	Q(t)	kg	1000
	1.6	Load centre distance	c	mm	600
	1.8	Load distance, centre of drive axle to fork	x	mm	945 [1)]
	1.9	Wheelbase	y	mm	1170 [1)]
Weight	2.1	Service weight including battery according to 6.5		kg	107
	2.2	Axle load, with load, drive/castor/fork wheel		kg	386/360
	2.3	Axle load, without load, drive/castor/fork wheel		kg	82/12
Wheels	3.1	Steer/fork wheels: Powerthane (Po), Steel (S), Nylon (N), Polyurethane (P), Rubber (R), Rubber antistatic (Ra)			P/Po, N, P
	3.2	Wheel size, front			175x50
	3.3	Wheel size, rear			85x100 / 85x75 [2)]
	3.5	Wheels, number front/rear (x=driven wheels)			1/2 or 1/4 [2)]
	3.6	Track width, front	b_{10}	mm	520/685
	3.7	Track width, rear	b_{11}	mm	364/529
Dimensions	4.4	Lift	h_3	mm	115
		Lift height	h_{23}	mm	200
	4.9	Height of tiller in drive position, min./max.	h_{14}	mm	1220
	4.15	Height, lowered	h_{13}	mm	85
	4.19	Overall length	l_1	mm	1575
	4.20	Length to face of forks	l_2	mm	415
	4.21	Overall width	b_1/b_2	mm	520/685
	4.22	Fork dimensions	s/e/l	mm	45/156/1150 [3)]
	4.25	Width over forks	b_5	mm	520/685
	4.32	Ground clearance, centre of wheelbase	m_2	mm	40
	4.33	Aisle width for pallets 1000 x 1200 crossways	A_{st}	mm	1525 [1)]
	4.34	Aisle width for pallets 800 x 1200 lengthways	A_{st}	mm	1725 [1)]
	4.35	Turning radius	W_a	mm	1370 [1)]
Performance	5.1	Travel speed, with/without load		km/h	3.5/5
	5.3	Lowering speed, with/without load		m/s	Controlable
	5.7	Gradeability. with/without load		%	—
	5.8	Max. gradeability with/without load		%	—
	5.10	Service brake			3.0 Nm
Electric motor	6.1	Drive motor rating S2 60 min		kW	0.2
	6.4	Battery voltage, nominal capacity K_5		V/Ah	2 x 12/24
	6.5	Battery weight		kg	2 x 9.5
Others	8.1	Type of drive control			Push button
	8.4	Sound level at the driver's ear according to DIN 12 053		dB(A)	63

1) Distance with forks raised
2) Single wheel / Boggie wheel
3) Other fork length available: 800/910/1000/1070/1220

All data are based on table configuration. Other configurations may give other values.
Truck performance and dimensions are nominal and subject to tolerances.
Specifications are subject to change without notice.


l
280
h23
200
125
x
h13
200
65
280
h23
180
x
h3
h23
h13
h14
m2
s
y
85
122
l2
l
l1
b1
b10
e
b11
b5
wa

Truck features:

- The motorized hand pallet truck will eliminate the strain from pulling and pushing a Hand Truck. This 1000 kg capacity machine is another step towards an ergonomic workplace.
- Increased ergonomy, no strain on arms, shoulder and back.
- Increased productivity – thanks to safety features.
- Suitable for multiple indoor applications.
- Safety features includes: emergency stop key, safety switch against collision and tow bar switch for the two end positions of the tow bar.
- Built-in charger with a separate charging cable.
- Also available in low fork height (U-model) with minimum height 75 mm.
- This product has been environmentally declared.

TP-Technical Publications, Sweden — 745346-040, version 1, 0908

TOYOTA

MATERIAL HANDLING

stronger together

TOYOTA INDUSTRIAL EQUIPMENT

TOYOTA MATERIAL HANDLING IN EUROPE, MANAGING THE TOYOTA AND BT MATERIALS HANDLING BRANDS IN EUROPE.